



SAE 10W-30

Synthetic Blend Motor Oil; API SN, ILSAC GF-5

## Product Description

**Ignix Avarar Synthetic Blend Motor Oils 10W-30 API SN, ILSAC GF-5** are formulated with a blend of conventional and synthetic base oils and a premium additive package. These oils are designed for use in carbureted, fuel injected, turbocharged gasoline engines. These oils exceed the performance requirements of API SN and ILSAC GF-5

## Typical Properties

### **SAE J300 Viscosity Grade**

### **10W-30**

Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	70.7
Viscosity @ 100°C, cSt, ASTM D445	10.9
Viscosity Index, ASTM D2270	145
CCS Apparent Viscosity, cP, ASTM D5293	5,000@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	9,800@-30°C
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-40

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

### **Exceeds Performance Requirements**

API SN, API SM, API SL, API SJ

ILSAC GF-5

Chrysler MS6395

GM6094M

Ford WSS-M2C945-A (10W-30)

### **Product Code**

SAE 10W-30

