



SAE 5W-20

Synthetic Blend Motor Oil; API SN, ILSAC GF-5

Product Description

Ignix Avarar Synthetic Blend Motor Oils SAE 5W-20 API SN, ILSAC GF-5 are formulated with a blend of conventional and synthetic base oils and a premium additive package. These oils are designed for use in carbureted, fuel injected, turbocharged gasoline engines. These oils exceed the performance requirements of API SN and ILSAC GF-5

Typical Properties

SAE J300 Viscosity Grade	5W-20
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	48.95
Viscosity @ 100°C, cSt, ASTM D445	8.3
Viscosity Index, ASTM D2270	145
CCS Apparent Viscosity, cP, ASTM D5293	5,000@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-35°C
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-44

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

API SN, API SM, API SL, API SJ

ILSAC GF-5

Chrysler MS6395

GM6094M

Ford WSS-M2C945-A (5W-20)

Product Code

SAE 5W-20

