

# NEXUS

SAE 5W-20

Full Synthetic Motor Oil, API SP, ILSAC GF-6A

## Product Description

**Ignix Nexus SAE 5W-20** are premium full synthetic motor oils manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

These oils are formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

## Typical Properties

<b>SAE J300 Viscosity Grade</b>	<b>5W-20</b>
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	47.75
Viscosity @ 100°C, cSt, ASTM D445	8.3
Viscosity Index, ASTM D2270	150
CCS Apparent Viscosity, cP, ASTM D5293	4,800@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	15,000@-35°C
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-44

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

## Exceeds Performance Requirements

API SP with Resource Conserving, API SN Plus, API SN  
 ILSAC GF-6A, GF-5  
 GMdexos1™ Gen 2  
 Chrysler MS6395  
 Ford WSS-M2C945-B1 (5W-20)

## Product Code

SAE 5W-20

