

10W-40

TORQUE ONE

4T (Four Stroke) Synthetic Blend Engine Oil SAE 10W-40 API SN, JASO MA2

Product Description

Ignix Torque One 4T Synthetic Blend Engine Oil (Four-Stroke) is a parasynthetic, high-performance, multi-grade lubricant for use in high-RPM, 4-stroke motorcycle engines with integral gear boxes and wet clutches as well as for use in any application requiring a four-stroke engine oil meeting the requirements of JASO MA2, JASO MA or API SL. Blended with synthetic basestocks and premium performance additives, Ignix Torque One 4T Synthetic Blend Engine Oil (Four-Stroke) provides excellent protection during rapid RPM increase. Specialty friction modifiers provide for smooth clutch and gear shift operation while specialty anti-oxidants and sophisticated dispersant technology provide enhanced cleanliness. Ignix Torque One 4T Synthetic Blend Engine Oil (Four-Stroke) is highly shear stable therefore eliminating viscosity breakdown. This product is a parasynthetic multi-grade engine oil suitable for use in all seasons.

Typical Properties

SAE J300 Viscosity Grade

Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	97.25
Viscosity @ 100°C, cSt, ASTM D445	14.5
Viscosity Indox ACTM D2270	ורר

Viscosity Index, ASTM D2270 CCS Apparent Viscosity, cP, ASTM D5293 5,200@-25°C 23,000@-30°C MRV Apparent Viscosity, cP, ASTM D4684 Flash Point, °C, ASTM D92 215 Pour Point, °C, ASTM D97 -40

*The values shown are typical of current production. Some are contro led in the manufacturing process, while others are not. A l of them may vary within tolerable ranges.

Suitable for Use:

APS SL, JASO MA2, JASO MA

Product Code

SAE 10W-40



