

TORQUE ONE

4T (Four Stroke)

Synthetic Blend Engine Oil

SAE 20W-50 API SN, JASO MA2

Product Description

Ignix Torque One 4T Synthetic Blend Engine Oil (Four-Stroke) is a parasyntetic, high-performance, multi-grade lubricant for use in high-RPM, 4-stroke motorcycle engines with integral gear boxes and wet clutches as well as for use in any application requiring a four-stroke engine oil meeting the requirements of JASO MA2, JASO MA or API SL. Blended with synthetic basestocks and premium performance additives, **Ignix Torque One 4T Synthetic Blend Engine Oil (Four-Stroke)** provides excellent protection during rapid RPM increase. Specialty friction modifiers provide for smooth clutch and gear shift operation while specialty anti-oxidants and sophisticated dispersant technology provide enhanced cleanliness. **Ignix Torque One 4T Synthetic Blend Engine Oil (Four-Stroke)** is highly shear stable therefore eliminating viscosity breakdown. This product is a parasyntetic multi-grade engine oil suitable for use in all seasons.

Typical Properties

SAE J300 Viscosity Grade	20W-50
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	160.55
Viscosity @ 100°C, cSt, ASTM D445	18.5
Viscosity Index, ASTM D2270	130
CCS Apparent Viscosity, cP, ASTM D5293	7,000@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-20°C
Flash Point, °C, ASTM D92	220
Pour Point, °C, ASTM D97	-30

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Suitable for Use:

API SL, JASO MA2, JASO MA

Product Code

SAE 20W-50

