



Ignix Voltura MULTI-VEHICLE ATF VI

Product Description

Ignix Voltura Formulated with synthetic base stocks and premium performance additives, Ignix Voltura SYNTHETIC MULTI-VEHICLE ATF is a premium-grade, low-viscosity synthetic automatic transmission lubricant. This product contains a premium performance additive package designed for excellent oxidation stability and thermal resistance, as well as excellent friction modification properties. Ignix Voltura SYNTHETIC MULTI-VEHICLE ATF is a multipurpose automatic transmission lubricant that is suitable for use in applications that require GM DEXRON® VI as well as a variety of North American, Asian, and European passenger car applications requiring low viscosity ATF.

Typical Properties

Parameter	Result	
Appearance, Visual	Red, Dyed Liquid	
Viscosity @ 40°C, cSt, ASTM D445	29.5	
Viscosity @ 100°C, cSt, ASTM D445	6.0	
Viscosity Index, ASTM D2270	155	
CCS Apparent Viscosity, cP, ASTM D5293	12,000	
Flash Point, °C, ASTM D92	190	
Pour Point, °C, ASTM D97	-52	

^{*}The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. A lof them may vary within tolerable ranges.

Suitable for Use:

Suitable for Use1:- Ford MERCON®*, MERCON®V*, MERCON® SP*, MERCON®LV*

- General Motors DEXRON®-II(E), DEXRON-III(G,H), DEXRON-VI
- BMW LT 71141, LA2634, M-1375.4, 7045-E, ETL-8072B · Chysler ATF +3 (SM7176-E)*, ATF +4 (MS9602)*
- Aisin Warner AW-1
- Honda/Acura DW-1, ATF-Z1
- Hyundai/Kia/Mitsubishi Diamond SP, SP-II, SP-III
- Isuzu ATF-II, ATF-III, Genuine ATF
- Mazda ATF 3317, F-1, FZ/S-1/N-1, M-III, M-V
- MB236.12*, MB 236.14*, MB 236.15*
- Nissan 402, Matic D/J/K/S

- Alison TES-389*, C-4
- Hyundai/Kia SP-IV, SPH-IV/SP4-M
- Idemitsu ATF HP. K17
- JASO M315 Class 1A* and 2013, 1A-LV
- MB236.41/5/6/7/8/9/91/10/11, NAG-1
- Mitsubishi ATF-J2, ATF-J3
- Subaru ATF, ATF 5AT, ATF-HP

Product Code



