



# LANTRA

## GEO 717

SAE 30, SAE 40, SAE 15W-40

### Product Description

Available in SAE 30, SAE 40 or SAE 15W-40 viscosities **Ignix Lantra GEO 717** is a family of Low-Ash Natural Gas Engine Oils. Designed for use in use in high-output, 4-stroke cycle natural gas engines operating under heavy loads in a variety of temperatures, **Ignix Lantra GEO 717** is optimal for applications including crude oil and gas transmission pipelines, electrical power generators, gas compressors, irrigation water pumps and well drilling rigs. Utilizing Group II Base Oil Technology as well as premium performance additives, this oil is fortified to provide ample protection against wear, oxidation, corrosion, varnish, and sludge, while maintaining excellent engine cleanliness. The low-ash, low-phosphorous additive technology is optimized to exceed the requirements of gas engines utilizing catalysts for exhaust treatment. **Ignix Lantra GEO 717** exceeds the performance requirements of API CD/CC.

### Typical Properties

SAE VISCOSITY GRADE	SAE 30	SAE 40	SAE 15W-40
Appearance, Visual	Amber, Viscous, Liquid		
API Performance	CD/CC	CD/CC	CD/CC
Viscosity cSt @ 40°C	91	132	124
Viscosity cSt @ 100°C	11.2	14.5	14.5
Pour Point, °F	-25	-15	-33
Flash Point, °F	405	412	140
Viscosity Index	110	109	118
Sulfated Ash	0.44	0.44	0.44
TBN	4.25	4.25	4.25

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

### Suitable for Use:

**Ignix Lantra GEO 717** is recommended for use in natural gas engines manufactured by the following:

- Caterpillar
- Dresser Rand (Category I, II, III)
- Ruston
- Waukesha
- Climax
- Minneapolis Moline
- Superior
- Worthington
- Colt-Fairbanks Morse
- Nordberg
- Wartsila

### Product Code:

SAE 30

SAE 40

SAE 15W-40

