

HARDLINE HARDLINE

Tractor Hydraulic Fluid

Product Description

Ignix Hardline PREMIUM TRACTOR HYDRAULIC FLUID is formulated with high-viscosity index base stocks and premium performance additives. This multipurpose oil is designed for use in transmissions, differentials, hydraulic, and power-steering units in many different makes of tractors and farm equipment. Designed for all-season use, this multi-grade oil is specialty blended to prevent rust, corrosion, foaming and oxidation. This oil exceeds the performance of John Deere's J20C specification.

Typical Properties

Parameter	Result
Appearance, Visual	Amber, Liquid
Viscosity @ 40°C, cSt, ASTM D445	55
Viscosity @ 100°C, cSt, ASTM D445	9.5
Viscosity Index, ASTM D2270	147
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-40

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Suitable for Use:

John Deere - J20C

New Holland (Ford) - FNHA-2-C-201.00 (M2C134-D), M2C41-B, M2C48-B, M2C53-A, M2C134-A, M2C134-B, M2C134-C, M2C86-B

Massey-Ferguson - M1135, M1141, M1143, M1110, M1127, M1129-A

Case International - MS-1209 – HyTran ULTRA R, MS-1207 – HyTran Plus, JIC-145/MS-1210, JIC-185/MS-1204, MS-1205, MS-1206, B-6

Kubota, White Farm - Q-1826, Q-1705, Q-1766, Q-1802,

Allison C-4,

Caterpillar TO-2

Denison HF-O, HF-1, HF-2 A

Sperry Vickers I-286-S, M-2950-S R

Sundstrand Hydraulics | Plessey-Sundstrand, Steiger, Versatile, Deutz-Allis, Landini, Fiat-Hesston

Product Code

