

HARDLINE HARDLINE

Super Tractor Oil Universal SAE 10W-30 & SAE 15W-40

Product Description

Ignix Hardline Super Tractor Oil Universal SAE 10W-30 and SAE 15W-40 are premium multi-purpose tractor lubricants designed for use in engines, transmissions, final drives and hydraulic systems of various off-road equipment. These multi-use fluids are formulated with group II paraffinic base stocks and a premium performance additive package which provides robust anti-wear, anti-oxidant, anti-foam, and detergent properties. Further, specialty friction modifiers minimize chatter, sticking or slipping for wet brakes and power take-off clutches. These -multi-grade fluids are designed for year-round performance in all seasons.

Typical Properties

SAE j300 Viscosity Grade	10W-30	15W-40
Appearance, Visual	Amber, transparent, Liquid	
Viscosity @ 40°C, cSt, ASTM D445	67.25	103.4
Viscosity @ 100°C, cSt, ASTM D445	10.5	14.5
Viscosity Index, ASTM D2270	145	145
CCS Apparent Viscosity, cP, ASTM D5293	5,500@-25°C	5,950@-20°C
MRV Apparent Viscosity, cP, ASTM D4684	21,000@-20°C	18,500@-15°C
Flash Point, °C, ASTM D92	215	225
Pour Point, °C, ASTM D97	-35	-32

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements:

API CF-4, CF, CE, CD/SF	ZF TE ML 06B, 07B
API GL-4	Ford M2C 159 B/C
Massey Ferguson MF 1145, 1144	Ford New Holland 82009201/2/3
Massey Ferguson MF 1139 (10W-30)	
John Deere J27C	

Product Code

SAE 10W-30

SAE 15W-40

